



**Product Code** PSEURO-30

**Description**

30A 12v EURO 5 & EURO 6 engine leisure battery charging system. Stop start Systems Used for Smart Alternator charging systems & Vehicles with Regenerative Braking, ( Mercedes Benz Blue Efficiency Vehicles, VW Blue Motion Vehicles, Ford ECONetic vehicles, Vauxhall ecoFlex vehicles to name a few).



**Specification**

OUTPUT LOAD CURRENT: 30A Max  
INPUT VOLTAGE: 12V nominal (9-32v)  
NO LOAD INPUT CURRENT: 2mA @ 12v input  
EMC: E11 Approved CE approved  
PROTECTION: Automatic overload and over temperature protection with fully automatic reset  
OUTPUT VOLTAGE: 12V  
ISOLATION: Non-isolated  
OPERATING TEMPERATURE: Maximum 70oC. Minimum -30oC  
SIZE AND WEIGHT: Length: 180mm, Height: 46mm, Width: 124mm, 700g

Suitable for: Most Lead Acid, Gel, AGM batteries  
Fan less cooling for zero noise

**Approvals** E11 Approval-Immunity requirements UNECE regulation 1 0 issue 4 Which covers all aspects of STANDARDS: EN50489:201 0 & CE Approval-Immunity to requirements of

12V INPUT	POSITIVE	RED
12V OUTPUT	POSITIVE	WHITE
COMMON	NEGATIVE	BLACK
CONTROL	POSITIVE	YELLOW

**Box Contents**

Charger, 500mm flying leads of thin wall auto cable, Manual